



Style A = Mounted with brass bushing

Style B = Without bushing

Style A	Style B	Dimensions (mm)										Mounting
D1 (D10)	D1 (D10)	D3 (max.)	R	N	A	B1	B2	C	H1 (± 0,2)	H2 (max.)	M	Bolt
-	20	45	R 1/4	12	110	50	35	18	30	56	75	M 10
-	25	60	R 1/4	15	140	60	40	25	40	75	100	M 12
-	30	60	R 1/4	15	140	60	40	25	40	75	100	M 12
25	35	80	R 1/4	15	160	60	45	25	50	95	120	M 12
30	40	80	R 1/4	15	160	60	45	25	50	95	120	M 12
35	45	90	R 1/4	19	190	70	50	30	60	110	140	M 16
40	50	90	R 1/4	19	190	70	50	25	60	110	140	M 16
45	55	100	R 1/4	24	220	80	55	35	70	125	160	M 20
50	60	100	R 1/4	24	220	80	55	35	70	125	160	M 20
55	65	120	R 1/4	24	240	90	60	35	80	145	180	M 20
60	70	120	R 1/4	24	240	90	60	35	80	145	180	M 20
70	80	140	R 1/4	28	270	100	70	45	90	165	210	M 24
75	90	160	R 1/4	28	300	100	80	45	100	185	240	M 24
80	90	160	R 1/4	28	300	100	80	45	100	185	240	M 24
90	100	180	R 1/4	28	330	120	90	45	100	195	270	M 24
90	110	180	R 1/4	28	330	120	90	45	100	195	270	M 24
100	120	200	R 3/8	28	360	120	100	50	110	215	300	M 24
110	125	200	R 3/8	28	360	120	100	50	110	215	300	M 24
120	140	220	R 3/8	35	410	140	100	55	120	235	330	M 30
125	140	220	R 3/8	35	410	140	100	55	120	235	330	M 30
130	150	220	R 3/8	35	410	140	100	55	120	235	330	M30
140	160	240	R 3/8	35	440	160	100	60	130	235	360	M 30
150	180	240	R 3/8	35	440	160	100	60	130	255	360	M 30