



Coupling Size	Type	Dimensions (mm)				STD bore	Bore metric		Bore inch		Weight (kg)	
		A	B	D	E		Min	Max	Min	Max	HUB	SPIDER
L035	1	16,0	20,5	6,6	—	3	3	8	1/8"	3/8"	0,01	0,001
L050	1	28,0	43,2	15,6	—	6	6	15	3/16"	5/8"	0,06	0,005
L070	1	35,0	50,8	19,0	—	9	9	19	3/16"	3/4"	0,12	0,008
L075	1	45,0	54,7	21,0	—	9	9	25	3/16"	1"	0,25	0,014
L090	1	54,0	54,7	21,0	—	9	9	28	3/16"	1 1/8"	0,37	0,018
L095	1	54,0	63,7	25,5	—	9	9	28	3/8"	1 1/8"	0,43	0,018
L099	1	64,5	72,5	27,0	—	12	12	35	7/16"	1 3/8"	0,67	0,031
L100	1	64,5	88,5	35,0	—	12	12	35	7/16"	1 3/8"	0,85	0,031
L110	1	85,0	108,0	43,0	—	15	15	48	1/2"	1 7/8"	1,84	0,06
L150	1	96,0	115,4	45,0	—	15	15	48	5/8"	1 7/8"	2,48	0,1
L109	2	115,0	133,4	54,0	101,6	19	19	55	5/8"	2 1/4"	3,63	0,14
L225	2	127,0	153,4	64,0	108,0	19	19	65	3/4"	2 5/8"	4,96	0,18